

SISTEMA MULTISPLIT INVERTER (UNIDAD EVAPORADOR PISO-TECHO)						
Modelo Sistema						
Modelo Condensadora (ODU)		MFM-I182H/HN120	MFM-I242H/HN121	MFM-I362H/HN117	MFM-I482H/HN117	MFM-I602H/HN118
Modelo Evaporador (IDU)		MFM-I182H/DLN120	MFM-I242H/DLN120	MFM-I362H/DLN116	MFM-I482H/DLN117	MFM-I602H/DLN118
<b>DESEMPEÑO</b>		<b>Unidades</b>				
Capacidad Nominal de Enfriamiento	Btu/h	18,000	24,000	36,000	48,000	60,000
Potencia entrada (modo enfriamiento)	Watts	1,440	1,920	4,509	5,161	5,500
SEER	Btu/Wh	20	20	16	18	18
EER	Btu/Wh	12.5	12.5	8.0	9.3	10.9
Capacidad Nominal Calefacción	Btu/h	18,000	24,000	38,000	50,000	60,000
Potencia entrada (modo Calefacción)	Watts	1,638	1,846	3,978	4,579	5,565
COP	Wt/We	3.22	3.81	2.80	3.20	3.16
<b>DATOS ELECTRICOS</b>		<b>Unidades</b>				
Voltaje /fase/ frecuencia	V-f-Hz	220 / 1 / 60	220 / 1 / 60	220 / 1 / 60	220 / 1 / 60	220 / 1 / 60
Protección recomendada	Amps	25	30	50	50	50
<b>ESPECIFICACIONES GENERALES</b>		<b>Unidades</b>				
Circulación de Aire (Hi /Mi / Lo)	m3/hr	932/825/715	1290/1204/1017	1762/1559/1084	2300/1900/1700	2353/1749/1352
Nivel de ruido Evap. (Hi /Mi / Lo)	dB(A)	44.5/41.5/36.5	50/47/39.5	51.5/0/40.5	55.5/51.5/46.5	55/50/39
Nivel de ruido Condensador	dB(A)	57.5	58.5	62.5	61.5	65
Distancias Máximas (Longitud Equiv.):						
En tubería Total	m	30	50	65	50	65
Entre niveles (Distancia vertical)	m	20	25	30	30	30
Diam. Tubería refrigerante (Liq /Gas)	mm(in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/19mm(3/4in)
Termostato	Std,	Remote Control	Remote Control	Remote Control	Remote Control	Remote Control
Diametro tubería drenaje	mm	ODΦ25	ODΦ25	ODΦ25	ODΦ25	ODΦ25
<b>DATOS FISICOS</b>		<b>Unidades</b>				
Peso Condensador (Neto/Bruto)	Kg	47.7/51	64/69	67.4/73	101/115	102.1/115.4
Peso Evaporador (Neto/Bruto)	Kg	25.9/31	26.5/31.4	31.3/37	39.8/46.4	46/50
Dimensiones Cond WxDxH	mm	845x363x702	946x410x810	946x410x810	952x415x1333	952x415x1333
Dimensiones Evap WxDxH	mm	1068x675x235	1068x675x235	1285x675x235	1650x675x235	1650x675x235
Contenedor de: 20'/40'/40'HQ - Cond	Pzas	102/215/216	44/96/138	44/96/138	22/48/48	22/48/48
Contenedor de: 20'/40'/40'HQ - Evap.	Pzas	102/220/252	102/220/252	92/188/213	72/147/167	72/147/167

